## **Maintenance**



# FIREFREE 88®

Water based intumescent paint

#### **MAINTENANCE**

Surfaces which have been coated with Firefree 88<sup>®</sup> should be protected from abuse and abrasion. Coated surfaces should be maintained to a clean appearance. Damaged surfaces should be repaired and Firefree 88<sup>®</sup> should be reapplied to the original specified dry film thickness to maintain the specific rating.

Carry out regular documented checks of the coated surfaces. Program repairs as soon as they become apparent.

### Cleaning:

Use a soft, lint-free cloth or sponge to wipe down the surface first. Avoid abrasive materials that can scratch or damage the paint. A soft-bristled brush, a non-abrasive sponge, or a micro-fibre cleaning cloth is recommended to avoid scratching or damaging any painted surfaces.

## **Repairing Painted Surfaces:**

- 1. Clean the surface.
- 2. Lightly abrade the surface to be repaired with sand paper, clean up and mask up area to be painted.
- 3. Apply primer if applicable.
- 4. Apply Firefree 88® intumescent coating.
- 5. Apply the topcoat and remove masking.

88

To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. User must contact Polymer Group Ltd to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Polymer Group Ltd quality control. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of products. Prices and cost data if shown, are subject to change without prior notice. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY THE SELLER, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OR LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.